



Product images may vary depending on the country layout

The cutting-edge waterproof AK-C7012 Medical Keyboard is specifically designed for areas where hygiene is crucial for. The disinfection capabilities makes it a perfect fit in hospitals and at medical practitioners, microbiological laboratories as well as industrial environments. The silicone key membrane protects the key pad against the ingress of dirt and fluids and promotes a thorough wipe disinfection. The ultra-flat key profile and the entirely closed surface is an effective barrier against cross contamination and the spread of germs. Equipped with the seamless closed membrane, the AK-C7012 corresponds to the requirements of the protection class IP68. Alternatively, it is available with a replaceable silicone cover that can be sterilized in an autoclave. The "CleanFunction" makes it possible to turn off the key pad while cleaning ("FN" + "Clean on/off").

FUNCTION AND PERFORMANCE

- - Compact Medical Keyboard for areas with strict cleaning protocols
- - Waterproof, gap-free design to protect the keyboard from liquids, dirt and debris
- - Ultra-flat key profile ensures maximum wipe disinfection while maintaining optimal haptics for an excellent typing experience
- - Approved for wipe disinfection according to CDC Guideline for Disinfection and Sterilization in Healthcare Facilities with EPA-registered disinfecting products

- - Fully sealed with IP68 rating or with a removable membrane that can be steam sterilized
- - CleanFunction enables the keys to be switched off during cleaning
- - Four 75 mm threaded holes for VESA mount

TECHNICAL DATA

Weight main product:	21 oz
Weight of product without packaging:	20.81 oz
Dimensions product without packaging:	14,37 in x 5,51 in x 0,67 in
Weight of product incl. packaging:	25.75 oz
Dimensions product incl. packaging:	14,96 in x 8,07 in x 0,98 in
Content of master carton (pieces):	20
Weight of master carton incl. content:	529.11 oz
Dimensions master carton:	15.75 in x 10.63 in x 17.6 in
Cable-length:	5.91 ft
Storage temperature:	-4 °F - 140 °F
Working temperature:	32 °F - 122 °F
Product approvals:	<ul style="list-style-type: none"> • CE • FCC • EN60601-1-2-2015 (IEC 4th edition)
System Requirements-Hardware:	USB-A
Operating system:	All operating systems that support USB keyboard interface
Scope of delivery:	<ul style="list-style-type: none"> • Keyboard • Manual
Switching characteristics:	tactile
Max. current consumption (mA) of keyboard:	100 mA
Actuating force (cN):	60 cN

Total Key Travel:	2,5 mm
Key labeling:	Silk screen printing on silicon membrane
Number of keys:	96
Special key functions:	<ul style="list-style-type: none">• FN Key• CleanFunction
Status LEDs:	in housing

Key technology:	Scissor
Keycap material:	ABS
Warranty:	2 years warranty

Errors, technical changes and delivery options reserved. Technical information refers only to the specification of the products. Properties are not guaranteed.

EAN & Part number	Protection class	Color	Illumination	Layout
7061117445705 AK-C7012F-UVS-W/FR	IP 68	white	no	FR (France)
7061114386346 AK-C7012F-UVS-W/GE	IP 68	white	no	DE (Germany)
7061117338182 AK-C7012F-UVS-W/NOR	IP 68	white	no	PN (PanNordic)
7061112222820 AK-C7012F-UVS-W/UK	IP 68	white	no	GB (United Kingdom)
7061115143207 AK-C7012F-U1-W/FR	Standard	white	no	FR (France)
7061112490373 AK-C7012F-U1-W/GE	Standard	white	no	DE (Germany)
7061116502836 AK-C7012F-U1-W/NOR	Standard	white	no	PN (PanNordic)
7061115784516 AK-C7012F-U1-W/UK	Standard	white	no	GB (United Kingdom)
7061112773582 AK-C7012F-U1-W/US	Standard	white	no	US (USA)