

AK-C7412 MEDICAL KEYBOARD COMPACT TP



Corded disinfectable Medical Keyboard with numpad and touchpad



Product images may vary depending on the country layout

The AK-C7412F keyboard series is particularly suitable for use in hospitals, doctors' offices and microbiology laboratories, as well as in industrial and administrative applications, thanks to its cleaning and disinfection capability.

The silicone membrane with the ultra-flat key profile reliably protects the keyboard against the ingress of dirt and liquids and enables thorough wipe disinfection. In addition, the closed, gap-free surface provides effective protection against cross-contamination, the spread of germs and the formation of biofilms.

Thanks to the fully sealed membrane, the AK-C7412 meets the requirements for protection class IP68.

The hygiene & medical keyboard is approved for clinical wipe disinfection with all common cleaning/disinfection agents in accordance with the VAH and DGHM guidelines.

Another advantage is the "CleanFunction", which allows the keypad to be locked during cleaning ("FN" + "Clean on/off").

FUNCTION AND PERFORMANCE

- - Waterproof, disinfectable Medical Keyboard keyboard
- - Approved for wipe disinfection with all common cleaning/disinfection agents in accordance with VAH guideline (German Association of Applied Hygiene)
- - Optimum typing comfort thanks to scissors balancing key technology

- - Perfect to use in areas with strict cleaning protocols
- - Fully sealed with IP68 rating
- - Clean function for deactivating the keypad during cleaning
- - 4 threaded holes 75mm for VESA mount
-

TECHNICAL DATA

Weight main product:	604 g
Weight of product without packaging:	600 g
Dimensions product without packaging:	365 mm x 139 mm x 17 mm
Weight of product incl. packaging:	720 g
Dimensions product incl. packaging:	390 mm x 180 mm x 25 mm
Content of master carton (pieces):	20
Weight of master carton incl. content:	13,300 g
Dimensions master carton:	400 mm x 273 mm x 447 mm
Cable-length:	180 cm
Storage temperature:	-20 °C - 60 °C
Working temperature:	0 °C - 50 °C
Product approvals:	<ul style="list-style-type: none">• CE• EU RoHS• FCC• EN60601-1-2-2015 (IEC 4th edition)
System Requirements-Hardware:	USB-A
Operating system:	All operating systems that support USB keyboard interface
Scope of delivery:	<ul style="list-style-type: none">• Keyboard• Manual
Switching characteristics:	tactile

Max. current consumption (mA) of keyboard:	32 mA
Actuating force (cN):	60 cN
Total Key Travel:	2,5 mm
Key labeling:	Silk screen printing on silicon membrane
Number of keys:	105
Special key functions:	<ul style="list-style-type: none"> • FN Key • CleanFunction

Status LEDs:	in housing
Key technology:	Scissor
Keycap material:	ABS
Protection class:	IP 68
Warranty:	2 years warranty

Errors, technical changes and delivery options reserved. Technical information refers only to the specification of the products. Properties are not guaranteed.

EAN & Part number	Protection class	Color	Layout
7061119932685 AK-C7412F-GUS-W/FR	IP 68	white	FR (France)
7061117428074 AK-C7412F-GUS-W/GE	IP 68	white	DE (Germany)
7061119200609 AK-C7412F-GUS-W/NOR	IP 68	white	PN (PanNordic)
4025112099519 AK-C7412F-GUS-W/UK	IP 68	white	GB (United Kingdom)