



 Lexmark™

Lexmark XC2342

Exceptional performance, secure and sustainable



Lexmark XC2342

With exceptional performance and secure design, the XC2342 multifunction printer (copy/scan/print/fax) delivers enhanced productivity, up to 40 ppm* on A4 paper and toner yields up to 20,000 pages** mono, and up to 11,700 pages** colour. Fast time to first print, superior print quality and easy-to-use touchscreen.

Secure by design

Lexmark's expertise helps customers safeguard their data, devices, and networks. Our comprehensive security ecosystem is built to address even the most complex data protection challenges. We've now enhanced this framework with the Trusted Platform Module (TPM)***, which provides on-board authentication, system integrity checks, and cryptographic capabilities to generate a unique digital system fingerprint.

Proprietary technology

We own our core technologies across hardware, firmware, services, and solutions—enabling seamless integration and minimising the risk of security gaps between your documents, devices, and network.

Sustainability

With certifications including Energy Star®, Blue Angel, RoHS, and EPEAT® Silver, the XC2342 is built for sustainability—today and into the future. Lexmark is an industry leader in the use of recycled content, with products incorporating at least 42% post-consumer recycled (PCR) materials and a continued focus on improvement. This product is also engineered for long life, designed to last and reduce waste.



Intelligent Design

The 17.8 cm touchscreen operator panel provides standard access to built-in workflow solutions such as Scan Centre—an intuitive app that simplifies routing to multiple destinations simultaneously—and Shortcut Centre, which allows users to create personalised shortcuts for frequent copy, fax, and e-mail tasks. The embedded solutions framework also enables businesses to add the apps that matter most—either by selecting from our library or developing custom solutions.

Manageability

These IoT-ready devices support remote management, including setup, configuration, consumables monitoring, and diagnostics. Firmware updates can also be deployed remotely, making it easy to upgrade to the latest applications and security features.

Ongoing Professional Product Support

From easy installation to handling high-volume output over time, our devices are designed to be intuitive and user-friendly. Support resources include instructional and on-device videos, as well as simple, colour-coded guidance for maintenance tasks like toner replacement—making the user experience truly world-class.

This is a Class A device according to international electromagnetic emissions standards (i.e. FCC Rules, EN 55022/EN 55032, etc.). Class A products are intended for use in non-residential/non-domestic environments. Use of a Class A product in residential/domestic environments may cause interference to radio communications and require corrective measures.

* Print speeds measured in accordance with ISO/IEC 24734 (ESAT). For more information see: www.lexmark.com/ISOspeeds.

** Average yield based on approximately 5% print coverage. In demonstration of circular economy principles, genuine Lexmark supplies with Unison™ Toner may contain components recovered from the Lexmark Cartridge Collection Programme (LCCP). Lexmark Return Programme cartridges are subject to the terms and conditions of the Lexmark Return Programme. See lexmark.com/returnprogramme for more information. Regular cartridges without the terms and conditions of the Lexmark Return Programme are available on lexmark.com or through Lexmark Channel Partners.

*** The Trusted Platform Module (TPM) is not available in some countries.

Lexmark XC2342



- 1 **Multifunction product with 17.8 cm touch screen**
491.4 x 479 x 475.1 mm
- 2 **200-Sheet output bin**
Dimensions included as part of base model
- 3 **Single sheet multipurpose feeder**
Dimensions included as part of base model
- 4 **250-Sheet tray**
Dimensions included as part of base model
- 5 **650-Sheet Duo Tray**
132.1 x 424.2 x 416.6 mm
- 6 **550-Sheet Tray**
132.1 x 424.2 x 416.6 mm

- 7 **550-Sheet Tray**
132.1 x 424.2 x 416.6 mm
- 8 **Adjustable Stand**
521 x 653 x 625 mm
- 9 **Swivel Cabinet**
263 x 476 x 600 mm
- 10 **Convenience Stapler HV**
82 x 109 x 121 mm



P/N 50M7390	Hardware Lexmark XC2342
P/N 24B7620	Supplies Lexmark XC2342 Cyan 11.7K Toner Cartridge
24B7621	Lexmark XC2342 Magenta 11.7K Toner Cartridge
24B7622	Lexmark XC2342 Yellow 11.7K Toner Cartridge
24B7623	Lexmark XC2342 Black 20K Toner Cartridge
35S8500	Staple Cartridges
75MOW00	Lexmark CS531, 632, 639, CX532, 635, C2335, XC2335 30K Waste Toner Bottle
75M0ZK0	Lexmark CS531, 632, 639, CX532, 635, C2335, XC2335 Black Return Programme 150K Imaging Kit
75M0ZV0	Lexmark CS531, 632, 639, CX532, 635, C2335, XC2335 4-Colour Return Programme 150K Imaging Kit
P/N 47C4590	Paper Handling Convenience Stapler
50M7550	550-Sheet Tray
50M7650	650-Sheet Duo Tray
P/N 27X0805	Memory Options 500+ GB Hard Disk
57X9528	Intelligent Storage Device (ISD)
P/N 57X0300	Application Solutions Contact Authentication Device
57X0301	Contactless Authentication Device
82S1203	IPDS License
82S1204	Bar Code License
P/N 1021294	Connectivity USB (2 Meter) Cable
27X0800	RS-232C Serial Interface Card (ISP Backpack Kit)
57X7040	English Keyboard Kit
SPD0002	Surge Protective Device, 220-240V
P/N 3073173	Furniture Swivel Cabinet
40C2300	Adjustable Stand

Product Specifications

Lexmark XC2342

Printing	
Display	Lexmark e-Task 7-inch (17.8 cm) colour touch screen
Print Speed	Up to: Black: 40 ppm ¹ (A4) / Colour: 40 ppm ¹ (A4)
Time to First Page	As fast as: Black: 6.3 seconds / Colour: 6.3 seconds
Print Resolution	Black: 1200 x 1200 dpi, 4800 Color Quality / Colour: 4800 Color Quality, 1200 x 1200 dpi
Memory	Standard: 2048 MB / Maximum: 2048 MB
Hard Disk	Intelligent Storage Drive included; Magnetic Hard Disk (optional)
Recommended Monthly Page Volume	1500 - 10000 pages ²
Maximum Monthly Duty Cycle	Up to: 125000 pages per month ³
Copying	
Copy Speed	Up to: Black: 39.5 cpm ¹ (A4) / Colour: 39.5 cpm ¹ (A4)
Time to First Copy	as fast as: Black: 6.7 seconds / Colour: 6.6 seconds
Scanning	
ADF Scan	DADF (single pass Duplex)
A4/Ltr Duplex Scan Speed	Up to: Black: 98 / 104 sides per minute / Colour: 80 / 84 sides per minute
A4/Ltr Simplex Scan Speed	Up to: Black: 49 / 52 sides per minute / Colour: 40 / 42 sides per minute
ADF Paper Input Capacity	Up to: 100 pages 75 gsm bond
Faxing	
Modem Speed	ITU T.30, V.34 Half-Duplex, 33.6 Kbps
Supplies ⁴	
Laser Cartridge Yields	up to: 20,000 ⁵ -page Black Cartridge / up to: 11,700 ⁵ -page Colour (CMY) Cartridges
Cartridge(s) Shipping with Product	3,000 ⁵ -page Black Return Programme Toner Cartridge ⁵ , 2,000 ⁵ -page Colour (CMY) Return Programme Toner Cartridges ⁵
Paper Handling	
Included Paper Handling	200-Sheet Output Bin, Integrated Duplex, Single sheet multipurpose feeder, 250-Sheet Tray
Optional Paper Handling	650-Sheet Duo Tray, 550-Sheet Tray
Paper Input Capacity	Up to: Standard: 251 pages 75 gsm bond / Maximum: 2001 pages 75 gsm bond
Paper Output Capacity	Up to: Standard: 200 pages 75 gsm bond / Maximum: 200 pages 75 gsm bond
Media Types Supported	Vinyl Labels, Paper Labels, Card Stock, Plain Paper, Envelopes, Refer to the Paper & Specialty Media Guide
Media Sizes Supported	A6, Oficio, 7 3/4 Envelope, 9 Envelope, JIS-B5, A4, Legal, A5, Hagaki Card, Letter, B5 Envelope, Statement, C5 Envelope, Executive, Universal, DL Envelope, Folio, 10 Envelope
General Information ⁶	
Standard Connectivity	Gigabit Ethernet (10/100/1000), Front USB 2.0 Specification Hi-Speed Certified port (Type A), Rear USB 2.0 Specification Hi-Speed Certified port (Type A), 802.11a/b/g/n/ac + Apple iBeacon, USB 2.0 Specification Hi-Speed Certified (Type B)
Noise Level	Operating: 53 dBA (Print) / 52 dBA (Copy) / 44 dBA (Scan)
Specified Operating Environment	Altitude: 0 - 2900 Metres (9,500 Feet) / Humidity: 15 to 80% Relative Humidity / Temperature: 10 to 32.2°C (50 to 90°F)
Product Guarantee	1-Year Onsite Service, Next Business Day
Size / Weight	H x W x D: 491.4 x 479 x 475.1 mm / 27.05 kg
ENERGY STAR Typical Electricity Consumption	TEC: 0.57 kilowatt-hours per week

All information is subject to change without notice. Lexmark is not liable for any errors or omissions.

¹ Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds.

² "Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage. ³ "Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs. ⁴ Product functions only with replacement cartridges designed for use in a specific geographical region. See www.lexmark.com/regions for more details. ⁵ Average continuous black or continuous composite CMY declared cartridge yield up to this number of standard pages in accordance with ISO/IEC 19798. ⁶ Printers are sold subject to certain license/agreement conditions. See www.lexmark.com/printerlicense for details.

This is a Class A device according to international electromagnetic emissions standards (i.e. FCC Rules, EN 55022/EN 55032, etc.). Class A products are intended for use in non-residential/non-domestic environments. Use of a Class A product in residential/domestic environments may cause interference to radio communications and require corrective measures.

© 2025 Lexmark. All rights reserved.

Lexmark, the Lexmark logo and Unison are trademarks of Lexmark International, Inc., registered in the United States and/or other countries.

Apple and AirPrint are trademarks of Apple Inc., registered in the U.S. and other countries. MOPRIA®, the Mopria® Logo™ and the Mopria® Alliance logos are registered trademarks and service marks of Mopria Alliance, Inc. in the United States and other countries. Unauthorised use is strictly prohibited. ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental Protection Agency. EPEAT® is a trademark of the Green Electronics Council in the United States and other countries. All other trademarks are the property of their respective owners.

This product includes software developed by the OpenSSL Project for use in the Open SSL Toolkit (<http://www.openssl.org/>).